



## SEALDECK ROOFING SEAM TAPE

Ultra-bonding flashing tape to seal around doors, roof and windows. It is designed for air/vapour barrier and provide a secondary waterproof protection. It can also be used as a transition membrane. 12 mil thick self-adhesive tape composed of an acrylic based adhesive and a polyolefin facer. The underface is covered with a split-release silicone film. It can be used in different types of environments, wet, hot and cold climates.

### Benefits:

- Very Good adhesion to most commons building materials without primers
- Can remain exposed to UV up to 270 days
- Self-sealing around nails, staples and screws
- Easy installation with split liner
- Meets requirements of AAMA711-22 level III

- Very good adhesion even at low temperature

### Storage/Handling:

When stored outdoor, the product should be covered with UV protection to prevent degradation from the sun. Storage temperature between 5° C to 40° C (41° F to 104° F).

The product need to be protected from open flame or other ignition sources during storage, shipping, and installation.

The product should always be properly installed and stored.

### PACKING INFORMATION

SKU	SD12
Color	White
Length per roll	75' (22.8m)
Width per roll	2" / 4" / 6" / 8" / 9"

### Technical Data:

Properties	Standard	Technical Value
Sealability around nail	ASTM D1970	Pass
Maximum load	ASTM D2523-13	MD: 5.1 kN/m XMD: 4.5 kN/m
Elongation at break	ASTM D2523-13	MD: 600% XMD: 400%
Adhesion to facer at 23° C (73° F)	ASTM D3330	14 lbs/in
Adhesion to Aluminum plate at 23° C (73° F)	ASTM D3330	12 lbs/in
Adhesion to Plywood at 23° C (73° F)	ASTM D3330	7 lbs/in
Low temperature flexibility	ASTM D1970	No crack at -28.9° C (-20° F)